Appln. No. 09/717,767

Attorney Docket No. 5709-159

## I. <u>Listing of Claims</u>

1. (Currently Amended): A two piece weatherstrip for a motor vehicle comprising, in combination,

a cover including a first flange portion, a second flange portion and a centrally disposed web, said first and second flange portions defining an outer surface,

- a body including a first slot and an adjacent first face and an adjacent, oppositely disposed second slot and an adjacent second face, said first slot [[receiving said web and said second slot]] adapted to receive a flange of said motor vehicle and said second slot receiving said web, at least one wiper flange extending from said [[second]] first face, a flexible flange extending from said [[first]] second face and having a terminal portion for engaging said motor vehicle and including a curved recess between said terminal portion and said [[first]] second face, said curved recess receiving and engaging a complementary portion of one of said flange portions of said cover.
- 2. (Previously Presented): The two piece weatherstrip of Claim 1 wherein said one of said flange portions defines a rounded end and said recess of said body is complementarily rounded.
- 3. (Original): The two piece weatherstrip of Claim 1 further including flocking disposed on said at least one wiper flange.
- 4. (Original): The two piece weatherstrip of Claim 1 including at least two wiper flanges.
  - (Cancelled):
- 6. (Original): The two piece weatherstrip of Claim 1 wherein said body further includes an S-shaped metal insert.
- 7. (Original): The two piece weatherstrip of Claim 1 wherein said body includes pluralities of obliquely disposed webs in said slots.



Appin. No. 09/717,767

Attorney Docket No. 5709-159

- 8. (Original): The two piece weatherstrip of Claim 1 wherein said centrally disposed web of said cover includes an asymmetrical notch.
- 9. (Previously Presented): A two piece weatherstrip for a vehicle comprising, in combination,

a cover including first and second flanges defining an outer surface and a centrally disposed web extending from said cover on a side opposite said outer surface, and

a body including a pair of adjacent, oppositely disposed slots, one of said slots receiving said web of said cover and another of said slots adapted to receive an edge of said vehicle, a third flange extending from said body adjacent said one of said slots and having a flexible terminal portion for engaging a portion of said vehicle, a recess formed in said third flange receiving a complementary portion of one of said flanges of said cover and a wiper extending from said body adjacent said another of said slots for engaging a window.

- 10. (Original): The two piece weatherstrip of Claim 9 further including low-friction material on said wiper.
- 11. (Original): The two piece weatherstrip of Claim 9 wherein said body further includes an S-shaped metal insert.
- 12. (Previously Presented): The two piece weatherstrip of Claim 9 wherein one of said flanges defines a rounded end and said recess of said body is complementarily rounded to receive said radiused end.
- 13. (Original): The two piece weatherstrip of Claim 9 wherein said body includes pluralities of obliquely disposed webs in said slots.
- 14. (Original): The two piece weatherstrip of Claim 9 wherein said centrally disposed web of said cover includes an asymmetrical notch.



Apptn. No. 09/717,767

Attorney Docket No. 5709-159

15. (Previously Presented): A two piece outer belt weatherstrip for a vehicle door comprising, in combination,

a cover including first and second flanges defining an outer surface and a centrally disposed web, one of said first and said second flanges defining a curved end, and

a body including an S-shaped metal channel and defining a first slot and <u>a</u> second adjacent, oppositely disposed slot, one of said slots receiving said centrally disposed web of said cover and another of said slots adapted to receive a flange of said vehicle, a wiper flange extending from said body adjacent said another of said slots, a vehicle engaging flange extending from said body adjacent said one of said slots and having a complementary recess [[for]] receiving said curved end portion of said one of said first and second flanges.

- 16. (Original): The two piece outer belt weatherstrip of Claim 15 further including flocking disposed on said at least one wiper flange.
- 17. (Original): The two piece outer belt weatherstrip of Claim 15 wherein said body includes pluralities of obliquely disposed webs in said slots.
- 18. (Previously Presented): The two piece outer belt weatherstrip of Claim 15 wherein said centrally disposed web of said cover includes an asymmetrical notch.
- 19. (Original): The two piece outer belt weatherstrip of Claim 15 including at least two wiper flanges.

